



性能:
 额定电流: 3.0A
 额定电压: 12V
 耐电压: 500V
 接触电阻: 30mΩ MAX
 绝缘电阻: 500MΩ
 工作温度: -40℃~+85℃
 塑件(材质): LCP黑色
 接触点(材质): 铜合金, 触点镀金3U"

RECOMMENDED PCB LAYOUT
 TOP VIEW(.XX±0.05)

| PART NO. | DIM A | DIM B | DIM C |
|---------------|-------|----------|----------|
| BC-2-414-C01 | 8.0 | 5.70±0.3 | 6.85±0.3 |
| BC-2-414A-C01 | 9.25 | 6.95±0.3 | 8.10±0.3 |
| BC-2-414B-C01 | 10.50 | 8.20±0.3 | 9.35±0.3 |

| NO. | PARTS | MATERIAL | QTY. | FINISHING |
|-----|------------------|-----------------|------|-----------|
| 2 | HOUSING | LCP | 1 | BLACK |
| 1 | CONTACT TERMINAL | PHOSPHOR BRONZE | 3 | Au PLATED |

DISONG ELECTRONIC CO., LTD.

COPYRIGHT RESERVED, PLEASE DO NOT COPY.

| PART NAME | | CONNECTOR | | DRAWING | | G.B.Wu | | DWG.No. | | DS-BC-86 | |
|-----------|--|------------------------|--|---------|--|----------|--|---------|--|------------|--|
| PART NO. | | BC-2-414 414A 414B-C01 | | CHECK | | Q.L.Dai | | REV. | | A0 | |
| UNIT : | | TOLERANCE | | ANGLE | | APPROVAL | | DATE | | 03-09-2012 | |
| mm | | OTHERWISE | | 0°±3' | | SCALE | | PAGE | | 1 OF 1 | |
| | | UP TO 5 ±0.2 | | | | 2:1 | | | | | |
| | | ABOVE 5 30 ~ ±0.3 | | | | | | | | | |
| | | ABOVE 30 ±0.5 | | | | | | | | | |
| | | ANGLE ±3' | | | | | | | | | |